This listing of claims will replace all prior versions, and listings, of claims in the application.

## **Listing of Claims:**

Claim1 (amended). A system for <u>selectively</u> observing the presence of at least one fluorophore in a test material to be used with a source of ultraviolet incident light comprising:

- a) a screen holder;
- b) a wavelength conversion screen receivable in and removable form from said screen holder comprising a scintillator which absorbs light of ultraviolet wavelengths and emits light of a narrow bandwidth  $\lambda_{s1}$  to  $\lambda_{s2}$ ; and
- c) a test material comprising at least one fluorophore positioned such that light passing through the wavelength conversion screen is incident on the material, a detector operable to detect a fluorophore emission wavelength  $\lambda_{dm}$  emitted by a the fluorophore having an excitation wavelength  $\lambda_{dx}$ , in which  $\lambda_{s1} < \lambda_{dx} < \lambda_{s2}$ , and which emits lights at a wavelength  $\lambda_{dm}$  which is detectable by a detector.

Claim 2 (amended). A <u>The</u> system according to claim 1 <u>further</u> comprising the <u>a</u> source of <del>U.V.</del> <u>ultraviolet light</u>.

Claim 3 (amended). A <u>The</u> system according to claim 2, in which wherein the source is a mercury vapour vapor lamp.

Claim 4 (amended). A <u>The</u> system according to claim 2, in which wherein the light source is a transilluminator and wherein the wavelength conversion screen, and the test material are arranged sequentially on the transilluminator whereby light passes through each of them.

Claim 5 (amended). A <u>The</u> system according to claim 1, wherein the <u>band-width bandwidth</u>  $\lambda_{s2}$  -  $\lambda_{s1}$  is less than 100 nm.

## RESPONSE TO 28 JUNE 2005 OFFICE ACTION U.S. PATENT APPLICATION NO. 10/748,368

Claim 6 (amended). A <u>The</u> system according to claim [[5]] <u>1</u>, wherein the bandwidth  $\lambda_{s2}$  -  $\lambda_{s1}$  is <u>from in the range-10</u> to 75 nm.

Claim 7 (amended). A <u>The</u> system according to claim 1, wherein  $\lambda_{dx}$  is in the range 370 – 720 nm.

Claim 8 (amended). A <u>The</u> system according to claim 1 wherein the value of  $\Delta d$ -where  $\Delta \lambda_{dx}$ - $\lambda_{s25}$  is less than 100 nm, and wherein  $\Delta = \lambda_{dx} - \lambda_{s2}$ .

Claim 9 (amended). A <u>The</u> system according to claim 1-in which the fluorophore/scintillator-combinations are selected from the combinations in Table 1, wherein:

the fluorophore is selected from the group consisting of Pyrene, AMCA, Cascade Blue,
Diethylaminocoumarin, Fluorescein, BODIPY FL, SYBR Green I, SYBR Green I, Acridine
Orange, Rhodamine 110, Oregon Green 488, Alexa 488, Rhodamine Green, Eosin, Alexa 532,
2',7'-Dimethoxy-4',5'-dichloro-6-carboxyfluorescein, Naphthofluoroscein, Alexa, Ethidium
bromide, Cy3, Tetramethylrhodamine, Rhodamine 6G, Alexa 568, Lissamine, Rhodamine,
Rhodamine Red, Carboxy-X-rhodamine, Texas Red, BODIPY TR, BODIPY 630/650, BODIPY
650/665, Cy5, Rhodamine 800, and Oxazine 750; and

the scintillator comprises a luminescent center selected from the group consisting of Ce<sup>3+</sup>/Tb<sup>3+</sup>, Tb<sup>3+</sup>, Mn<sup>4+</sup>; Tl<sup>+</sup>, Eu<sup>2+</sup>, Tm<sup>3+</sup>, Rm<sup>3+</sup>, Mn<sup>2+</sup>, Dy<sup>3+</sup>, and Eu<sup>3+</sup>.

Claim 10 (amended). A <u>The</u> system according to claim 1 in which the wavelength conversion screen absorbs lights of wavelength less than  $\lambda_{s1}$ -whereby substantially no light of suchwavelengths is incident on the test material.

Claim 11 (amended). A The system according to claim 1, in which wherein:

the detector is operable to detect a first fluorophore emission wavelength  $\lambda_{dx}$  emitted by a first fluorophore and a second fluorophore emission wavelength  $\lambda_{dx}$  emitted by a second fluorophore;

the first emission wavelength is different from the second emission wavelength; and each fluorophore the test material has at least two fluorophores distributed in it, each of which has an absorption maximum in the range  $\lambda_{s1}$  to  $\lambda_{s2}$  and which have different emission wavelengths  $\lambda_{dx}$ .

Claim 12 (canceled).

Claim 13 (canceled).

Claim 14 (canceled).

Claim 15 (amended). A <u>The</u> system according to claim 1 in which the detector is an automated device and is a component of the system.

Claim 16 (amended). A system for observing the presence of a fluorophore in a test material comprising:

- a) a source of ultraviolet light which is comprising a mercury vapour lamp;
- b) a holder for a screen;
- c) an exchangeable wavelength conversion screen adapted to be receivable in the screen holder and to be removable therefrom, and comprising a scintillator which absorbs light of ultraviolet wavelengths and emits light of a narrow bandwidth  $\lambda_{s1}$  [[-]] to  $\lambda_{s2}$ , where the bandwidth  $\lambda_{s2}$   $\lambda_{s1}$  is less than 100 nm;
  - d) a support for a test material; and

e) a test material which comprises a fluorophore having an excitation wavelength  $\lambda_{dx}$  and an emission wavelength  $\lambda_{dm}$ ; and f) a detector capable of detecting light of an emission wavelength  $\lambda_{dm}$  generated by a fluorophore contained in a test material, the fluorophore having an excitation wavelength  $\lambda_{dx}$ ;

wherein the support allows the <u>test material</u> <u>fluorophore</u> to be positioned on the opposite side of the screen to the light source and the detector is located on the side of the test material opposite to the screen.

Claim 17 (amended). The system of claim 16 in which the screen comprises, in sequence, a substrate—which is transparent to ultraviolet light, a wavelength converting layer which comprises the scintillator, and a protective layer overlying the wavelength converting layer which is transparent to light of wavelength in the range  $\lambda_{s1}$  [[-]] to  $\lambda_{s2}$ .

Claim 18 (amended). The system of claim 16 in which the scintillator comprises a luminescent centre-center selected from the group consisting of Ce<sup>3+</sup>/Tb<sup>3+</sup>, Tb<sup>3+</sup>, Mn<sup>4+</sup>; TI<sup>+</sup>, Eu<sup>2+</sup>, Tm<sup>3+</sup>, Rm<sup>3+</sup>, Mn<sup>2+</sup>, Dy<sup>3+</sup>, and Eu<sup>3+</sup>.

Claim 19 (amended). The system according to claim 18, wherein the scintillator further comprises which comprises a matrix in which the luminescent centre is included, selected from the group consisting of CeMgAl<sub>11</sub>O<sub>19</sub>, Y<sub>2</sub>O<sub>2</sub>S, Gd<sub>2</sub>O<sub>2</sub>S, LaPO<sub>4</sub>, Y<sub>5</sub>SiO<sub>5</sub>, GdMgB<sub>5</sub>O<sub>10</sub>, (CaZn)<sub>3</sub>(PO<sub>4</sub>)<sub>2</sub>, SrB<sub>4</sub>O<sub>7</sub>, (SrMg)<sub>2</sub>P<sub>2</sub>O<sub>7</sub>, YVO<sub>4</sub>, and MgGa<sub>2</sub>O<sub>4</sub>.

Claim 20 (amended). The system of claim 19 in which the scintillator comprises a the luminescent center comprises Tm<sup>3+</sup> centre and an yttrium vanadate the matrix comprises YVO<sub>4</sub>-matrix.

- Claim 21 (amended). A method for observing the presence of at least one fluorophore in a test material using a detector, the method comprising the steps of:
- a) providing an exchangeable, <u>first</u> wavelength conversion screen comprising a <u>first</u> scintillator which absorbs light of ultraviolet wavelengths and emits light of a narrow <u>band width</u> <u>bandwidth</u>  $\lambda_{s1}$  [[-]] <u>to</u>  $\lambda_{s2}$ ;
- b) directing incident ultraviolet light through the wavelength conversion screen whereby light having a wavelength in the range  $\lambda_{s1}$  to  $\lambda_{s2}$  is transmitted through the screen;
- c) providing a test material, which comprises comprising a first fluorophore which that absorbs light at an excitation wavelength around a maximum  $\lambda_{dx}$ , in which  $\lambda_{s1} < \lambda_{dx} < \lambda_{s2}$ , and that emits light at a wavelength  $\lambda_{dm}$ ;
- d) causing the transmitted light of wavelength in the range  $\lambda_{s1} \lambda_{s2}$  to pass into said test material whereby the fluorophore emits light at said wavelength  $\lambda_{dm}$ ; and
- e) detecting said emitted light using a detector system which is sensitive to light of wavelength  $\lambda_{dm}$ .

Claim 22 (original). The method of claim 21 in which  $\lambda_{s2}$  -  $\lambda_{s1}$  is less than 100 nm.

Claim 23 (amended). The method of claim 21, wherein in which in which the fluorophore/scintillator combinations are selected from the combinations in Table 1

the fluorophore is selected from the group consisting of Pyrene, AMCA, Cascade Blue, Diethylaminocoumarin, Fluorescein, BODIPY FL, SYBR Green I, SYBR Green I, Acridine Orange, Rhodamine 110, Oregon Green 488, Alexa 488, Rhodamine Green, Eosin, Alexa 532, 2',7'-Dimethoxy-4',5'-dichloro-6-carboxyfluorescein, Naphthofluoroscein, Alexa, Ethidium bromide, Cy3, Tetramethylrhodamine, Rhodamine 6G, Alexa 568, Lissamine, Rhodamine, Rhodamine Red, Carboxy-X-rhodamine, Texas Red, BODIPY TR, BODIPY 630/650, BODIPY 650/665, Cy5, Rhodamine 800, and Oxazine 750; and

the scintillator comprises a luminescent center selected from the group consisting of Ce<sup>3+</sup>/Tb<sup>3+</sup>, Tb<sup>3+</sup>, Mn<sup>4+</sup>; TI<sup>+</sup>, Eu<sup>2+</sup>, Tm<sup>3+</sup>, Rm<sup>3+</sup>, Mn<sup>2+</sup>, Dy<sup>3+</sup>, and Eu<sup>3+</sup>. Claim 24 (amended). The method of claim 21, wherein in which the test material has further comprises a second fluorophore at least two fluorophores distributed in it, wherein the first and second fluorophore each of which has an absorption maximum in the range  $\lambda_{s1}$  to  $\lambda_{s2}$  and which have different the emission wavelength of the first fluorophore is different from the emission wavelengths wavelength  $\lambda_{dm}$  of the second fluorophore.

Claim 25 (amended). The method of claim 21 in which the test material has a further comprises a second fluorophore distributed in it which has having an absorption envelope  $\lambda_{db}$  outside the range  $\lambda_{s1}$  to  $\lambda_{s2}$  wherein the method further comprises:

- f) providing a second wavelength conversion screen which comprises a second scintillator which absorbs light of UV wavelength and emits light at a higher wavelength  $\lambda_{dbm}$  in the range  $\lambda_{sb1}$  to  $\lambda_{sb2}$ , the second scintillator selected such that  $\lambda_{sb1} < \lambda_{db} < \lambda_{sb2}$ ;
  - g) exchanging the first screen for the second screen;
- h) directing incident ultraviolet light through the second wavelength conversion screen whereby light having a wavelength in the range  $\lambda_{sb1}$  to  $\lambda_{sb2}$  is transmitted;
- i) causing the transmitted light having a wavelength in the range  $\lambda_{sb1}$  to  $\lambda_{sb2}$  to pass into the test material, whereby the second fluorophore emits light of wavelength  $\lambda_{dbm}$ ; and
- j) detecting said emitted light of wavelength  $\lambda_{dbm}$  using a detector which is sensitive to light of wavelength  $\lambda_{dbm}$ .

Claim 26 (amended). The method of claim 21 in which the <u>first</u> scintillator comprises a luminescent-centre center selected from the group consisting of Ce<sup>3+</sup>/Tb<sup>3+</sup>, Tb<sup>3+</sup>, Mn<sup>4+</sup>; TI<sup>+</sup>, Eu<sup>2+</sup>, Tm<sup>3+</sup>, Rm<sup>3+</sup>, Mn<sup>2+</sup>, Dy<sup>3+</sup>, and Eu<sup>3+</sup>.

Claim 27 (amended). The method of claim 26, wherein in which the luminescent centre is incorporated into a matrix selected from the group consisting of CeMgAl<sub>11</sub>O<sub>19</sub>, Y<sub>2</sub>O<sub>2</sub>S, Gd<sub>2</sub>O<sub>2</sub>S, LaPO<sub>4</sub>, Y<sub>5</sub>SiO<sub>5</sub>, GdMgB<sub>5</sub>O<sub>10</sub>, (CaZn)<sub>3</sub>(PO<sub>4</sub>)<sub>2</sub>, SrB<sub>4</sub>O<sub>7</sub>, (SrMg)<sub>2</sub>P<sub>2</sub>O<sub>7</sub>, YVO<sub>4</sub>, and MgGa<sub>2</sub>O<sub>4</sub>.

Claim 28 (amended). The method of claim 26 in which the scintillator comprises a Tm<sup>3+</sup>-centre center and the matrix comprises an yttrium vanadate-YVO<sub>4</sub>-matrix.

Claim 29 (amended). The method of claim 21 in which the <u>first</u> fluorophore is selected from the group consisting of Pyrene, AMCA, Cascade Blue, Diethylaminocoumarin, Fluorescein-(FAM), BODIPY FL, SYBR Green I, SYBR Green I, Acridine Orange, Rhodamine 110, Oregon Green 488, Alexa 488, Rhodamine Green, Eosin, Alexa 532, 2',7'-Dimethoxy-4',5'-dichloro-6-carboxyfluorescein-(JOE), Naphthofluoroscein, Alexa, Ethidium bromide, Cy3, Tetramethylrhodamine, Rhodamine 6G, Alexa 568, Lissamine, Rhodamine, Rhodamine Red, Carboxy-X-rhodamine-(ROX), Texas Red, Fluorophore label, BODIPY TR, BODIPY 630/650, BODIPY 650/665, Cy5, Rhodamine 800, and Oxazine 750.

Claim 30 (amended). The method of claim 21 in which the <u>first</u> fluorophore is fluorescein.

Claim 31 (amended). The method of claim 27 in which the <u>first</u> fluorophore is fluorescein.

Claim 32 (new). A method for selectively illuminating a fluorophore comprising:

- a) providing an exchangeable wavelength conversion screen comprising a scintillator that absorbs light of ultraviolet wavelengths and emits light of a narrow bandwidth  $\lambda_{s1}$  to  $\lambda_{s2}$ ;
- b) directing incident ultraviolet light through the wavelength conversion screen whereby light having a wavelength in the range  $\lambda_{s1}$  to  $\lambda_{s2}$  is transmitted through the screen;
- c) providing a test material comprising a first fluorophore and a second fluorophore, wherein

the first and second fluorophores absorb light at an excitation wavelength around a maximum  $\lambda_{dx}$ , in which  $\lambda_{s1} < \lambda_{dx} < \lambda_{s2}$ ,

the first and second fluorophores emit light at a wavelength  $\lambda_{dm}$ , and

## RESPONSE TO 28 JUNE 2005 OFFICE ACTION U.S. PATENT APPLICATION NO. 10/748,368

the first fluorophore emission wavelength  $\lambda_{dm}$  is different from the second fluorophore emission wavelength  $\lambda_{dm}$ ;

- d) causing the transmitted light of wavelength in the range  $\lambda_{s1} \lambda_{s2}$  to pass into said test material to cause either the first fluorophore or the second fluorophore to emit its respective emission wavelength  $\lambda_{dm}$ ; and
- e) detecting the emitted light using a detector system which is sensitive to light of the emitted wavelength  $\lambda_{dm}$ .

Claim 33 (new). The method according to claim 32, wherein the bandwidth  $\lambda_{s2}$  -  $\lambda_{s1}$  is less than 100 nm.

Claim 34 (amended). The system according to claim 32, wherein the bandwidth  $\lambda_{s2}$  -  $\lambda_{s1}$  is from 10 to 75 nm and wherein  $\lambda_{dx}$  is in the range 370 – 720 nm.